

Denso BHT-1100 Series (Windows OS Terminal)
Источник: <https://www.denso-adc.com/bht-1100-series/>

Model Number: BHT-1171BWB-CE (with camera) / BHT-1170BWB-CE (without camera)

System:
Operating System: Windows Embedded CE6.0 R3
CPU: 32bit RISC 800MHz
RAM: 512MB
Flash ROM: 2.0GB
Card Slot: microSDHC x 1

Display:
Resolution: 3.5 in. HVGA (320 x 480 px)
Backlight: LCD

Scanner:
Camera: 1.3 megapixels (BHT-1171BWB-CE only)
Method: Advanced Scan Plus (CCD)
Readable 1D Barcodes: EAN-13/8 (JAN-13/-8), UPC-A/-E, UPC/EAN (with add-on), Interleaved 2 of 5, Standard 2 of 5, CODABAR (NW-7), CODE39, CODE93, CODE128, GS1-128 (EAN-128), GS1 DataBar (RSS)
Minimum Resolution 1D Barcodes: 0.125mm
Scanning Distance: 640mm (resolution 0.33mm), 1300mm (resolution 1.0mm)
Keypad: 21 keys (including power key) + cross cursor key + 3 trigger keys

Wireless LAN Communication:
Standard: IEEE802.11b/g/n
Frequency: 2.4GHz
Communication Distance: Indoor 150m, Outdoor 300m
Security: WEP40/128, WPA-PSK, WPA2-PSK, WPA-1x, WPA2-1x, 802.1x

Bluetooth: Bluetooth Ver2.0 + EDR Class 2
Cradle I/F: RS-232C / USB client

Power:
Main Battery: Lithium-ion Battery
Operating Time: Approx. 17 hours (standard battery) / Approx. 25 hours (large capacity battery)

Operating Environment:
IP Rating: IP54
Temperature Range: -20 to 50°C
Drop Test: 1.5m drop on concrete floor, 10 times each on all 6 sides (total 60 times)

Physical Characteristics:
Weight: Approx. 380g (with camera) / Approx. 375g (without camera)