

Denso BHT-805B (BHT-800 Series, End of Sale)

Источник: https://www.denso-wave.com/en/adcd/product/handy_terminal/bht-800.html

Type: BHT-805B (Batch model, Barcode)

OS: BHT-OS

CPU: 32bit RISC CPU

Memory: 32 MB (user file area approx. 21 MB)

Display size: 2.6 inch, QVGA (240x320 dots)

Display device: Liquid crystal dot matrix color display

Backlight: White LED

Scanner: Advanced Scan (CCD)

Readable barcodes: EAN-13/8(JAN-13/8), UPC-A/E, UPC/EAN (with add-on), Interleaved 2 of 5, CODABAR(NW-7), CODE39, CODE93, CODE128, GS1-128(EAN-128), RSS(GS1 DataBar)

Minimum resolution barcodes: 0.125mm

Key pad: 25 keys (incl. power key) + 2 trigger keys

Communications:

Optical I/F: Infrared (IrDA Ver.1.3 Low Power), transmission speed up to 4Mbps

Transmission distance: approx 0.15m max

Power supply: Lithium-ion battery

Operation hours: Approx. 33 hours

Environment Requirements:

Operating temperature: -20°C to 50°C

Protection rating: IP54

Drop resistance: 0.2m x 1000+ times/6 faces, each of 10 concrete floor from 1.2m (60 times total) / 2.0m

Weight (incl. battery): Approx. 220g