

GOLE F9A

Источник: <https://www.golerugged.com/rugged-tablet/358.html>

Key Features | IP67, 10.1"IPS + N150 + 16GB +256GB + WiFi 2.4G&5G Dual band + 1000Mbps + RS-232(DB9)+ USB3.2 + Type-C + Windows11 Pro

System Physical Standard Configuration:

Type | Details | Descriptions

Product Form | Form Factor | IP67 Rugged Tablet PC

Dimensions | 280x184x26.5mm

Weight | 1.15KG

LCD | Screen Size | 10.1"

Screen Resolution | 1200*1920 (IPS+HD+300ANSI) (Standrd)

TP | Touch Module | G+G Multi-Touch (10 Points)

Battery | Type | Rechargeable lithium polymer

Capacity | 8000mAh/7.6V

Working Time | Over 8 hours (FHD local video display)

System Hardware Configuration:

Type | Details | Descriptions

CPU | Type | Intel Alder Lake-N150 (Quad-core)

Speed | 3.4GHz

GPU | Type | Intel® UHD Graphics

Memory | Capacity | 16GB LPDDR5

Storage | eMMC | 256GB

Camera | Front | 500M

Rear | 13000M

Speaker | Built-in | 8Ω/1W*2pcs with water proof

Micphone | Built-in | Yes

G-sensor | Built-in | Yes

Light-sensor | Built-in | Optional

Network Connections:

Type | Details | Descriptions

WIFI | RTL8821CE-VC | Wi-Fi Dual-band 1T1R 11ac + Bluetooth 5.0

Bluetooth | RTL8821CE-VC | Bluetooth 5.0

4G LTE | Optional | Optional (Mini PCI-E slot)

QR code Scanners | Optional | Optional

GPS | BD2/GPS/Glonass (Choose two of the three) | Optional

NFC | Optional | Optional

Fingerprinter | Optional | Optional

RFID | UHF band | Optional

Ethernet Network | RJ-45 | 1000Mbps Gigabit Lan

Interface Configuration:

Type | Details | Descriptions

Type-C | Type-C 3.1 | x1pc (Full functionality)

USB Interface | USB3.2 | x2pcs

SD / TF Card reader | TF Card reader | x1pc (up to 512GB)

SIM Card Slot | SIM Slot for 4G LTE | x1pc

Audio Jack | 3.5mm standard headphone+Microphone | x1pc

COM Port | DB9 (RS232) | x1pc

Button Switch:

Type | Details | Descriptions

Power | On/Off | x1pc

Volume | Down/UP | x1pc

HotKey | Hot Key for QR Scanner | x1pc

Forced outage | Power restart when push restart button | x1pc

Main Accessories:

Type | Details | Descriptions

Power adapter | DC 12V/3A | x1pc

User's Manual | User's Manual | x1pc

Handle Straps | Handle straps and hand clasping | Optional

Extension Docking | USB2.0; Power charging; RJ45; RS232 | Optional

Vehicle Bracket | USB2.0; Power charging; RJ45; RS232 | Optional

Software Configuration:

Type | Details | Descriptions

Power on Function | By Power Button or Auto Power on | Optional

Wake up on Lan | Wake up on Lan by RJ45 | Yes

PXE | Preboot Execution Environment | Yes

Operating System | Windows 11 Pro or above | Yes (Official Windows license is Optional)

Environment:

Temperature | Operation Temperature | -10°C ~ 55°C (1080p or 4K local video display)

Storage Temperature | -20°C ~ 70°C (Restore to Operation Temperature 2hr before use)

Humidity | Operating Humidity | 35% ~ 80% relative humidity, Non-condensing

Storage Humidity | 20% ~ 93% relative humidity, Non-condensing

Certification:

IP67 | IP67 Certification | Yes

CE | CE-Red | Yes