

GOLE F11J

Источник: <https://www.golerugged.com/rugged-tablet/408.html>

Standard Configuration: 11.6 inch rugged tablet pc Intel Celeron N5105/N5095/N5100 8GB/16GB

Type | Details | Descriptions

Product Form | Form Factor | 11.6 inch Rugged Tablet PC

Weight | 1.05kg

Dimensions | 315.3*200.7*20.6mm

LCD | Screen Size | 11.6"

Screen Resolution | 1920x1080 (IPS+FHD+600ANSI) (Standrd)

TP | Touch Module | G+G Multi-Touch (5 Points)

Battery | Type | Rechargeable lithium polymer

Capacity | 809052 7.6V/5900mAh

Working Time | Over 4 hours (FHD local video display)

System Hardware Configuration:

Type | Details | Descriptions

CPU | Type | Intel Celeron N5105/N5095/N5100

Speed | 2.0GHz ~ 2.90GHz

GPU | Type | Intel UHD Graphics

Memory | Capacity | 8GB/16GB(Optional) LPDDR4X

Storage | eMMC | 128GB/256GB

SSD | Optional (m.2 NVME)

Camera | Front | 5M

Rear | 13M

Speaker | Built-in | 8Ω/1W*1pc with water proof

Micphone | Built-in | Yes

G-sensor | Built-in | Yes

Network Connections:

Type | Details | Descriptions

WIFI | WIFI+BT | Wi-Fi Dual-band 1T1R 11ac + Bluetooth 4.2

4G LTE | Optional | Optional (M.2)

GPS | BD2/GPS/Glonass (Choose two of the three) | Yes

Ethernet Network | RJ-45 | 1000Mbps Gigabit Lan

Interface Configuration:

Type | Details | Descriptions

Type-C | Type-C 3.2 | x1pc

USB Interface | USB3.0 | x1pc

SD / TF Card reader | TF Card reader | x1pc (up to 128GB)

HDMI | Micro HDMI | x1pc

SIM Card Slot | SIM Slot for 4G LTE | x1pc

Audio Jack | 3.5mm standard headphone+Microphone | x1pc

Button Switch:

Type | Details | Descriptions

Power | On/Off | x1pc

Volume | Down/UP | x1pc

Main Accessories:

Type | Details | Descriptions

Power adapter | 12V 3A | x1pc

User's Manual | User's Manual | x1pc

Software Configuration:

Operating System | Windows 11 Pro or above | Yes (Officoal Windows license is Optional)

Environment:

Temperature | Operation Temperature | -10oC ~ 55oC (1080p or 4K local video display)

Storage Temperature | -20oC ~ 70oC (Restore to Operation Temperature 2hr before use)

Humidity | Oprating Humidity | 35% ~ 80% relative humidity, Non-condensing

Storage Humidity | 20% ~ 93% relative humidity, Non-condensing

Certification:

CE | CE-Red | Optional

IP65 | IP65 Certification | Optional