

GOLE F7GA

Источник: <https://www.golerugged.com/rugged-tablet/136.html>

System Physical Standard Configuration:

Type | Details | Descriptions

Product Form | Form Factor | IP67 Rugged Tablet PC F7GA

Dimensions | 280×184×26.5mm

Weight | 1.15KG

LCD | Screen Size | 10.1"

Screen Resolution | 1200×1920 (IPS+FHD+600ANSI) (customized)

800×1280 (IPS+HD+300ANSI) (Standrd)

TP | Touch Module | G+G Multi-Touch; Used Gorilla glass from Corning

Battery | Type | Rechargeable lithium polymer

Capacity | 8000mAh/7.6V

Working Time | 8 hours (FHD local video display)

System Hardware Configuration:

Type | Details | Descriptions

CPU | Type | Intel Gemini lake N4120 (Quad-Core)

Speed | 1.1GHz ~ 2.6GHz (N4120)

GPU | Type | Intel UHD 600 Graphics

Memory | Capacity | 8GB LPDDR4

Storage | eMMC | 128GB

SSD | Optional (Mini PCI-E slot)

Camera | Front | 5M

Rear | 5M

Speaker | Built-in | 8Ω/1W*2pcs with water proof

Micphone | Built-in | Yes

G-sensor | Built-in | Yes

Light-sensor | Built-in | Optional

Network Connections:

Type | Details | Descriptions

WIFI | WIFI Module: Intel AC3165 | WIFI 802.11ac/b/g/n 2.4G&5Ghz Dual-band

Bluetooth | BT Module: Intel AC3165 | Bluetooth4.2

4G LTE | Optional | Yes(Mini PCI-E slot)

QR code Scanners | Standard | Optional

GPS | BD2/GPS/Glonass (Choose two of the three) | Yes

NFC | Optional | Optional

Fingerprinter | Optional | Optional

RFID | UHF band | Optional

Ethernet Network | RJ-45 | 1000Mbps Gigabit Lan

Interface Configuration:

Type | Details | Descriptions

Type-C | Type-C 3.1 (Video Out+Data+Power) | ×1pc

USB Interface | USB3.0 | ×2pcs

SD / TF Card reader | TF Card reader | ×1pc (up to 256GB)

SIM Card Slot | SIM Slot for 4G LTE | ×1pc

Audio Jack | 3.5mm standard headphone+Microphone | ×1pc

HDMI | Micro HDMI 2.0 | ×1pc (Output 4K@60fps UHD video)

COM Port | DB9 (RS232) | ×1pc

Button Switch:

Type | Details | Descriptions

Power | On/Off | ×1pc

Volume | Down/UP | ×1pc

HotKey | Hot Key for QR Scanner | ×1pc

Forced outage | Power restart when push restart button | ×1pc

Main Accessories:

Type | Details | Descriptions

Power adapter | DC 12V/3A | ×1pc

User's Manual | User's Manual | ×1pc

Handle Straps | Standard | ×1pc

Extension Docking | USB2.0; Power charging; RJ45; RS232 | Optional

Vehicle Bracket | USB2.0; Power charging; RJ45; RS232 | Optional

Software Configuration:

Type | Details | Descriptions

Power on Function | By Power Button or Auto Power on | Optional

Wake up on Lan | Wake up on Lan by RJ45 | Yes

PXE | Preboot Execution Environment | Yes

Security | TPM2.0 (Hardware) contained | Yes

Operating System | Windows 10 Pro | Yes

Ubuntu Linux | Test by end user

Environment:

Temperature | Operation Temperature | -10oC ~ 55oC (1080p or 4K local video display)

Storage Temperature | -20oC ~ 70oC (Restore to Operation Temperature 2hr before use)

Humidity | Operating Humidity | 35% ~ 80% relative humidity, Non-condensing

Storage Humidity | 20% ~ 93% relative humidity, Non-condensing

Certification:

IP67 | IP67 Certification | Yes

CE | CE-Red | Yes

MIL-STD-810G | Match the military standard of USA | Yes