

GOLE F7G Plus

Источник: <https://www.golerugged.com/rugged-tablet/133.html>

Key Features | F7G plus IP67, 10.1" IPS + J4105/N4120+8GB +128GB + WiFi 2.4G&5G
Dual band + 1000Mbps + HDMI1.4 + RS-232(DB9)+ USB3.0

System Physical Standard Configuration:

Type | Details | Descriptions

Product Form | Form Factor | IP67 Rugged Tablet PC

Dimensions | 280×184×26.5mm

Weight | 1.15KG

LCD | Screen Size | 10.1"

Screen Resolution | 1200×1920 (IPS+FHD+600ANSI) (Standrd)

800×1280 (IPS+HD+300ANSI) (Optional, For MOQ order)

TP | Touch Module | G+G Multi-Touch

Battery | Type | Rechargeable lithium polymer

Capacity | 16000mAh/3.7V

Working Time | Over 8 hours (FHD local video display)

System Hardware Configuration:

Type | Details | Descriptions

CPU | Type | Intel J4105/N4120 Quad-Core

Speed | 1.44GHz ~ 1.92GHz

GPU | Type | Intel HD Graphics Gen8

Memory | Capacity | 8GB

Storage | eMMC | 128GB

SSD | /

SATA 2.5" HDD | /

Camera | Front | 5M

Rear | 5M

Speaker | Built-in | 8Ω/1W with water proof

Micphone | Built-in | Yes

G-sensor | Built-in | Yes

Network Connections:

Type | Details | Descriptions

WIFI | WIFI Module: Broadcom AP6255/AP6256 | WIFI 802.11ac/b/g/n 2.4G&5Ghz Dual-band

Bluetooth | BT Module: Broadcom AP6255/AP6256 | Bluetooth4.0

3G/4G LTE | standard | standard

QR code Scanners | Optional | standard

NFC | Optional | standard

GPS | BD2/GPS | standard

Fingerprinter | Capacitive fingerprint sensor | Optional

Ethernet Network | RJ-45 | 1000Mbps Gigabit Lan

Interface Configuration:

Type | Details | Descriptions

USB Interface | USB3.0 | ×1pc

USB2.0 | ×2pcs (USB2.0 TypeA×1 + Micro USB2.0×1)

SD / TF Card reader | TF Card reader | ×1pc (up to 128GB)

SIM Card Slot | SIM Slot for 3G/4G LTE | standard

Audio Jack | 3.5mm standard | ×1pc

HDMI | Micro HDMI 1.4 | ×1pc

Video output through HDMI | Up to 4K

COM Port | DB9 (RS232) | ×1pc (External small PCBA)

Button Switch:

Type | Details | Descriptions

Power | On/Off | ×1pc

Volume | Down/UP | ×1pc

CMOS Reset | Reset by Short Press | /

Main Accessories:

Type | Details | Descriptions

Power adapter | DC 5V/3A | ×1pc

User's Manual | User's Manual | ×1pc

Handle Straps | Optional | standard

Extension Docking | USB2.0×1pc ; DC IN × 1pc | Optional

Software Configuration:

Type | Details | Descriptions

Wake up on Lan | Wake up on Lan by RJ45 | /

PXE | Preboot Execution Environment | /

Operating System | Windows 11 | Optional

Linux | Test by end user

Environment:

Temperature | Operation Temperature | -10oC ~ 55oC (1080p or 4K local video display)

Storage Temperature | -20oC ~ 70oC (Restore to Operation Temperature 2hr before use)

Humidity | Operating Humidity | 35% ~ 80% relative humidity, Non-condensing

Storage Humidity | 20% ~ 93% relative humidity, Non-condensing

Certification:

IP67 | IP67 Certification | Yes

Other | Other | Optional