

RFID Printer Series

Improving accuracy and visibility



Smart Labels. Smarter Business.

Empower operations with BIXOLON's advanced RFID labelling solutions.



Boost your business efficiency with BIXOLON's range of RFID label printers. Offering LCD displays with intuitive menus, simple calibration functions to read RFID labels and tag locations, alongside UHF RFID printing and encoding capabilities. Establish effective business solutions by adopting BIXOLON's RFID labelling for a range of applications in retail, logistics, manufacturing, healthcare and more.



Retail & Hospitality

RFID labelling enables faster, bulk item scanning without line-of-sight, ensuring accurate stock levels. Real-time tracking of assets and merchandise while reducing theft and the misplaced of items. While elevating customer experience.

Applications

- Inventory Accuracy & Visibility
- Loss Prevention
- Omni-channel Fulfillment
- Customer Experience



Transportation & Logistics

Streamline shipment verification, while reducing errors in shipping and receiving. Supporting real-time updates of cargo status and improves delivery reliability. Assists with regulatory compliance and chain-of-custody requirements.

Applications

- Parcel & Pallet Tracking
- Supply Chain Visibility
- Compliance & Security



Warehouse & Manufacturing

With support for RFID labels, staff can monitor production stages in real time and improve workflow visibility. Defects are quickly and accurately identified, while components for recalls are efficiently tracked.

Applications

- Receiving / Put-away Efficiency
- Inventory & Material Management
- Work-in-Progress (WIP) Tracking
- Quality Control & Traceability
- Tool & Equipment Tracking



Healthcare

BIXOLON RFID printers improve patient safety by enabling accurate wristband and specimen labelling for real-time identification and traceability. They enhance asset and inventory management, help track medical equipment, and pharmaceuticals efficiently to prevent loss and ensure compliance.

Applications

- Patient Safety & Identification
- Inventory Control
- Quality Care
- Pharmaceutical & Specimen Tracking



Government / Education

Enabling public sector organisations to accurately track assets, documents and equipment, while improving efficiency and reducing losses. BIXOLON RFID printers enhance security and compliance by maintaining chain-of-custody for sensitive materials and support real-time visibility for audits and accountability.

Applications

- Asset Tracking
- Security & Compliance
- Field Operations
- Document Management
- Book Identification



Why BIXOLON RFID Printers?

1 Meet Industry Standards

BIXOLON RFID printers remain fully compliant with evolving industry encoding standards such as ISO/IEC and GS1.

2 Fast and Accurate

Leveraging extensive field experience, BIXOLON delivers RFID solutions that offer high-speed printing and precise data encoding.

3 Numerous RFID Label Types

All types of RFID Labels (ISO 18000-6C) are supported, with rapid and seamless transitions between different label types, enhancing operational efficiency.

4 Reliable Durability

Built for reliability, BIXOLON printers combine rugged hardware with advanced technology to handle high workloads and deliver consistent RFID encoding.

5 User-Centred Functions

Easy setup through automatic calibration of RFID labels to streamline workflows for efficiency.

6 Professional Support

Our expert support team is readily available to resolve setup issues quickly, ensuring uninterrupted business operations.

BIXOLON RFID Printer Lineup

BIXOLON's growing range of RFID label printers support UHF RFID print and encoding technology, offering a minimum pitch of 0.6 inches (16mm) RFID inlay which reduces the expense of choosing interfaces. Available as Mobile, Desktop and Industrial printing formats, these highly versatile, multi-functional printing solutions are packed with premium features to boost businesses efficiency by improving accuracy and visibility.



XT6-40NR / XT5-40NR 4-inch (114 mm) Industrial RFID Label Printer **Ideal for high-volume stock labelling and cross-docking in central fulfillment hubs or large warehouses**

- Print speeds of up to 14ips at 203 dpi
- 5-inch (XT6-40NR), 4.3-inch (XT5-40NR) full-colour touch display
- USB, USB Host, Serial, Ethernet, Parallel, Bluetooth®, WLAN, GPIO
- Compatible with BIXOLON XPM™, XCM™ and SOTI® Connect



XD5-40ItR / XD5-40tR 4-inch (118 mm) Desktop RFID Label Printer **For offices, shipping depots, or small warehouses handling low-to-mid volume labelling**

- Print speeds of up to 6 ips (XD5-40tR), 8 ips (XD5-40ItR) at 203 dpi
- USB, USB Host, Serial, Ethernet, B/T, WLAN
- 2-inch Mono LCD display for easier setup and alert information
- Compatible with label design software; BIXOLON's Label Artist™ and Seagull's BarTender®



XM7-40R 4-inch (112 mm) Mobile RFID Label Printer **Enhancing efficiency for real-time stock audits, on-the-spot labelling of products, shipments or specimens**

- Print speeds of up to 5ips at 203 dpi
- Smart battery with capacity of 6800 mAh (USB Type-C® PD supported)
- USB, Serial, B/T, WLAN
- 1.8 m (6 ft.) drop rate and IP54 sealing
- Colour LCD display for easy setup

Specifications

	XT6-40NR	XT5-40NR
Print Characteristics		
Print Method	Thermal Transfer or Direct Thermal	Thermal Transfer or Direct Thermal
Print Speed	XT6-40NR: Up to 14 ips (356 mm/sec) XT6-43NR: Up to 12 ips (305 mm/sec) XT6-46NR: Up to 5 ips (127 mm/sec)	XT5-40NR: Up to 14 ips (356 mm/sec) XT5-43NR: Up to 10 ips (254 mm/sec) XT5-46NR: Up to 5 ips (127 mm/sec)
Print Resolution	XT6-40NR: 203 dpi, XT6-43NR: 300 dpi, XT6-46NR: 600 dpi	XT5-40NR: 203 dpi, XT5-43NR: 300 dpi, XT5-46NR: 600 dpi
Print Width	XT6-40NR: 104 mm XT6-43NR: 105.7 mm XT6-46NR: 105.6 mm	XT5-40NR: 104 mm XT5-43NR: 105.7mm XT5-46NR: 105.6 mm
Print Length	XT6-40NR: Up to 4,000 mm, XT6-43NR: Up to 2,500 mm, XT6-46NR: Up to 1,000 mm	XT5-40NR: Up to 4,000 mm, XT5-43NR: Up to 2,500 mm, XT5-46NR: Up to 1,000 mm
Sensor	Transmissive (Adjustable), Reflective (Adjustable), Ribbon-End, Head Open	Transmissive (Adjustable), Reflective (Adjustable), Ribbon-End, Head Open
Media Characteristics		
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	25 to 114 mm	25 to 114 mm
Media Roll Diameter	Up to 203 mm	Up to 203 mm
Media Thickness	0.06 to 0.30 mm XT6-40NR-M: On-metal RFID Labels of up to 1.5 mm	0.06 to 0.30 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Inner Core	38 to 76.2 mm	38.1 to 76.2 mm, 25.4 mm (Optional)
Ribbon Characteristics		
Ribbon Type	Wax, Wax/Resin, Resin, Outside or Inside	Wax, Wax/Resin, Resin, Outside, Inside
Ribbon Width	50 to 110 mm	50 to 110 mm
Ribbon Length	Up to 450 m	Up to 450 m
Core Inner Diameter	25.4 mm	25.4 mm
Physical Characteristics		
Dimensions (W x L x H)	Standard: 269 × 467 × 327 mm (10.59 x 18.39 x 12.87 inch) External Rewinder: 269 x 467 x 420 mm (10.59 x 18.39 x 16.54 inch)	Standard: 269 x 490 x 324 mm (10.59 x 19.29 x 12.76 inch) External Rewinder: 269 x 490 x 407 mm (10.59 x 19.29 x 16.02 inch)
Weight	Standard: 14.7 kg (32.41 lbs.) External Rewinder: 19.3 kg (42.55 lbs.)	Standard: 13.98 kg (30.82 lbs.) External Rewinder: 17.98 kg (39.64 lbs.)
Electrical	Internal Power AC/DC Adapter 100-240 VAC, 50-60 Hz	Internal Power Adapter 100-120 V/200-240 VAC, 50/60 Hz
Display	5-inch Touch TFT LCD	4.3-inch CTP Touch TFT LCD
Performance Characteristics		
Memory	1 GB SDRAM, 1 GB Flash	512 MB SDRAM, 512 MB Flash
Interface	Standard: USB + Serial + Ethernet + 2 USB Host ports Optional: Ⓞ USB + Serial + Ethernet + 2 USB Host ports + WLAN and Bluetooth® Ⓞ USB + Serial + Ethernet + 2 USB Host ports + Parallel Ⓞ USB + Serial + Ethernet + 2 USB Host ports + Parallel + WLAN and Bluetooth Ⓞ USB + Serial + Ethernet + 2 USB Host ports + GPIO Ⓞ USB + Serial + Ethernet + 2 USB Host ports + GPIO + WLAN and Bluetooth ----- Ethernet: 10/100/1000 Mbps (1Gbps) WLAN: 2.4G/5GHz, 802.11a/b/g/n/ac/ax (Infrastructure, Wi-Fi Direct, Soft AP) GPIO: DB15 (Female), 5/24 V, 4 GPI, 8 GPO	Standard: USB + Serial + Ethernet + 2 USB Host ports Optional: Ⓞ USB + Serial + Parallel or GPIO + Ethernet + 2 USB Host ports Ⓞ USB + WLAN + Ethernet + 2 USB Host ports Ⓞ USB + WLAN + Parallel + Ethernet + 2 USB Host ports Ⓞ USB + Bluetooth® + Ethernet + 2 USB Host ports Ⓞ USB + Bluetooth + Parallel + Ethernet + 2 USB Host ports ----- Ethernet: 10/100/1000 Mbps (1Gbps) WLAN: 2.4G/5GHz, 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) GPIO: DB15 (Female), 5/24 V, 4 GPI, 8 GPO
Real Time Clock	Supported	Supported
Environment Characteristics		
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 80 % RH Storage: 5 to 95% RH	Operating: 10 to 80 % RH Storage: 5 to 95% RH
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL), XML	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL), XML
Driver/Utility	Windows® Driver (Europlus/Seagull), Linux®/macOS® CUPS Driver, Virtual COM USB/Ethernet Driver, BIXOLON Utility, OPOS/JPOS Driver, Device Driver for SAP®. Network Auto Installer	Windows® Driver (Europlus/Seagull), Linux®/macOS® CUPS Driver, Virtual COM USB/Ethernet Driver, BIXOLON Utility, OPOS/JPOS Driver, Device Driver for SAP®. Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK, Web Print SDK (Android/iOS/Windows/macOS), XI(Optional), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK, Web Print SDK (Android/iOS/Windows/macOS), XI(Optional), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK
Design & Print	Label Artist-II™, Label Artist™ Web, Label Artist™ Mobile (Android/iOS), mPrint App (Android/iOS), BarTender® Ultralite for BIXOLON	Label Artist-II™, Label Artist™ Web, Label Artist™ Mobile (Android/iOS), mPrint App (Android/iOS), BarTender® Ultralite for BIXOLON
MDM (Optional)	BIXOLON Profile Manager-XPM™, XCM™ (Windows/Android), SOTI® Connect supported	BIXOLON Profile Manager-XPM™, XCM™ (Windows/Android), SOTI® Connect supported
Fonts/Graphics/Symbolologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbolologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories/Supplies		
Accessories	Power Cord	Power Cord
Options & Accessories	Peeler, Auto Cutter, Serial Cable, Parallel Cable, USB Cable, Rewinder (Internal: Max.O.D. 130 mm, External: Max.O.D. 203 mm), Cutter-Tray, Ribbon & Media Near End Sensor	Peeler, Auto Cutter, External Rewinder (Max.O.D. 203 mm), 1-inch I.D. Core Media Supply Hanger Serial Cable, Parallel Cable, USB Cable
Compatible Supplies	B-ribbon™	B-ribbon™
RFID		
Frequency	UHF, 865 to 928 MHz	UHF, 865 to 928 MHz
Transmit Power	1W	1W
Modulation	ASK	ASK
Protocol	ISO 18000-63 (EPC Class1 Gen2V2)	ISO 18000-63 (EPC Class1 Gen2V2)
Auto Cutter	Optional	Optional
Tag Pitch	Min 16 mm	Min 16 mm

Specifications

	XD5-40IItr	XD5-40tr
Print Characteristics		
Print Method	Thermal Transfer or Direct Thermal	Thermal Transfer or Direct Thermal
Print Speed	XD5-40IItr: Up to 8 ips (203 mm/sec) XD5-43IItr: Up to 6 ips (152 mm/sec)	XD5-40tr: Up to 6 ips (152 mm/sec) XD5-43tr: Up to 4 ips (102 mm/sec)
Print Resolution	XD5-40IItr: 203 dpi, XD5-43IItr: 300 dpi	XD5-40tr: 203 dpi, XD5-43tr: 300 dpi
Print Width	XD5-40IItr: Up to 108 mm, XD5-43IItr: Up to 105.7 mm	XD5-40tr: Up to 108 mm XD5-43tr: Up to 105.7 mm
Print Length	Up to 1,000 mm	Up to 1,000 mm
Sensor	Transmissive (Fixed), Reflective (Adjustable), Head Open, Ribbon-End	Transmissive (Fixed), Reflective (Adjustable), Head Open, Ribbon-End
Media Characteristics		
Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	15 to 118 mm	15 to 118 mm
Media Roll Diameter	Up to 127 mm	Up to 127 mm
Media Thickness	0.06 to 0.20 mm	0.06 to 0.20 mm
Supply Method	Easy Paper Loading	Easy Paper Loading
Inner Core	25.4 to 38.1 mm	25.4 to 38.1 mm
Ribbon Characteristics		
Ribbon Type	Wax, Wax/Resin, Resin, Outside	Wax, Wax/Resin, Resin, Outside
Ribbon Width	33 to 110 mm	33 to 110 mm
Ribbon Length	Up to 300 m	Up to 300 m
Core Inner Diameter	25.4 mm, 12.7 mm	25.4 mm, 12.7 mm
Physical Characteristics		
Dimensions (W x L x H)	210 x 284 x 188 mm (8.3 x 11.2 x 7.4 inch)	210 x 284 x 188 mm (8.3 x 11.2 x 7.4 inch)
Weight	2.48 kg (5.46 lbs.)	2.48 kg (5.46 lbs.)
Electrical	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz	EnergyStar® Certified, External Power Adapter 100-240 VAC, 50/60 Hz
Display	FSTN LCD (200 x 100 pixels)	FSTN LCD (200 x 100 pixels)
Performance Characteristics		
Memory	512 MB SDRAM, 512 MB Flash	256 MB SDRAM, 256 MB Flash
Interface	Standard: USB + USB Host + Serial + Ethernet Optional: Ⓞ USB + USB Host + Serial + Ethernet + WLAN Ⓞ USB + USB Host + Serial + Ethernet + Bluetooth WLAN: 2.4G/5GHz, 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Ethernet: 10/100Mbps	Standard: USB + USB Host + Serial + Ethernet Optional: Ⓞ USB + USB Host + Serial + Ethernet + WLAN Ⓞ USB + USB Host + Serial + Ethernet + Bluetooth ----- WLAN: 2.4G/5GHz, 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) Ethernet: 10/100Mbps
Real Time Clock	Supported (Optional)	Supported (Standard)
Environment Characteristics		
Temperature	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)	Operating: 0 to 41°C (32 to 105°F) Storage: -40 to 60°C (-40 to 140°F)
Humidity	Operating: 10 to 85% RH (Non-condensing) Storage: 5 to 95% RH	Operating: 10 to 85% RH (Non-condensing) Storage: 5 to 95% RH
Software		
Emulation	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL), XML	SLCS™, BPL-Z™ (ZPL II®), BPL-E™ (EPL™), BPL-D™ (DPL, Optional), XML(Optional)
Driver/Utility	Windows® Driver (Europlus/Seagull), Linux®/macOS® CUPS Driver, Virtual COM USB/Ethernet Driver, BIXOLON Utility, OPOS/JPOS Driver, Device Driver for SAP®, Network Auto Installer	Windows® Driver (Europlus/Seagull), Linux®/macOS® CUPS Driver, Virtual COM USB/Ethernet Driver, BIXOLON Utility, OPOS/JPOS Driver, Device Driver for SAP®, Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK, Web Print SDK (Android/iOS/Windows/macOS), XI (Optional), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK, Web Print SDK (Android/iOS/Windows/macOS), XI (Optional), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK
Design & Print	Label Artist-II™, Label Artist™ Web, Label Artist™ Mobile (Android/iOS), mPrint App (Android/iOS), BarTender® Ultralite for BIXOLON	Label Artist-II™, Label Artist™ Web, Label Artist™ Mobile (Android/iOS), mPrint App (Android/iOS), BarTender® Ultralite for BIXOLON
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android)	BIXOLON Profile Manager-XPM™, XCM™ (Windows/Android), SOTI® Connect supported
Fonts/Graphics/Symbologies		
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)	Bitmap Fonts (10 SLCS, 16 BPL-Z, 5 BPL-E, 9 BPL-D), Scalable Fonts (1 SLCS, 1 BPL-Z, 1 BPL-D), 23 Code page, Unicode supported (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos	Supporting user-defined fonts (TTF, TTE, FNT), graphics, formats and logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR code, TLC 39
Accessories/Supplies		
Included in the Box	AC/DC Adapter, Power Cord, USB Cable, Holder Ribbon x 2, Core Paper (0.5-inch, 1-inch)	AC/DC Adapter, Power Cord, USB Cable, Holder Ribbon x 2, Core Paper (0.5-inch, 1-inch)
Options & Accessories	Peeler, Auto Cutter, External Paper Supply, Serial Cable	Peeler, Auto Cutter, External Paper Supply, Serial Cable
Compatible Supplies	B-ribbon™, B-band™	B-ribbon™, B-band™
RFID		
Frequency	UHF, 865 to 928 MHz	UHF, 865 to 928 MHz
Transmit Power	1W	1W
Modulation	ASK	ASK
Protocol	ISO 18000-63 (EPC Class1 Gen2V2)	ISO 18000-63 (EPC Class1 Gen2V2)
Auto Cutter	Optional	Optional
Tag Pitch	Min 16 mm	Min 16 mm

Specifications

	XM7-40R
Print Characteristics	
Print Method	Direct Thermal
Print Speed	Up to 5 ips (127 mm/sec – Liner, Linerless)
Print Resolution	203 dpi
Print Width	Up to 104 mm
Print Length	-
Sensor	Paper End, Gap, Black Mark, Paper Cover Open, Peel-off
Media Characteristics	
Media Type	Liner, Notch Optional: Linerless, RFID Tag
Media Width	50 to 112 mm
Media Roll Diameter	Up to 66 mm
Media Thickness	0.07 to 0.19 mm
Supply Method	Easy Paper Loading
Inner Core	19 mm, 12 mm
Ribbon Characteristics	
Ribbon Type	-
Ribbon Width	-
Ribbon Length	-
Core Inner Diameter	-
Physical Characteristics	
Dimensions (W x L x H)	158 x 186 x 82 mm (6.23 x 7.33 x 3.23 inch)
Weight	Including battery: 1,130 g (2.50 lbs.) Paper: 360 g (0.79 lbs.)
Power (Nominal Capacity)	EnergyStar® Certified, External AC/DC Adapter, USB Type-C® Power Delivery Charging (Sink) Support Smart Battery (7.2V Li-ion, 6800 mAh, Under 6 Hours Charing Time)
Display	TFT LCD (IPS, 240 x 320 pixels)
Peeler	Supported
Media Holder	Supported (Inner Core: 19 mm)
Performance Characteristics	
Memory	Standard: 128 MB SDRAM, 256 MB Flash Optional: 256 MB SDRAM, 512 MB Flash USB 2.0 HS + Serial + Bluetooth + WLAN
Interface	----- WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) - WEP40/104, WPA1/2 (PSK, EAP) ----- Easy Bluetooth Pairing™ via NFC
Port	Power, USB Type-C, Serial/USB 14P, External Charging/Ethernet 12P
Environment Characteristics	
Temperature	Operating: -15 to 50°C (5 to 122°F) Storage: -30 to 70°C (-22 to 158°F)
Humidity	Operating: 10 to 80% RH
Sealing	IP54
Drop Rate	1.8 m (6 ft.)
Software	
Emulation	SLCS™, BPL-Z™ (ZPL II®)
Driver/Utility	Windows® Driver (Europlus/Seagull), Linux®/macOS® CUPS Driver, Virtual COM USB Driver, BIXOLON Utility, OPOS/JPOS Driver, Device Driver for SAP®, Network Auto Installer
Developer Tools	Android™/iOS®/Windows SDK, Linux SDK, Xamarin® SDK, Web Print SDK (Android/iOS/Windows/macOS), Cordova™ Plugin, MAUI SDK, Flutter™ Plugin, React Native® SDK
Design & Print	Label Artist-II™, Label Artist™ Web, Label Artist™ Mobile (Android/iOS), mPrint App (Android/iOS), BarTender® Ultralite for BIXOLON
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows/Android) SOTI® Connect supported
Fonts/Graphics/Symbologies	
Fonts	Bitmap Fonts (10 SLCS, 16 BPL-Z, 7 BPL-C), Scalable Fonts (1 SLCS, 1 BPL-Z) 23 Code Page, Unicode (UTF-8, UTF-16LE, UTF-16BE)
Downloadable Objects	Supporting User-Defined Fonts (TTF, TTE, FNT, CSF, CPF), Graphics, Formats, Layouts and Logos
Barcode Symbologies	1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB, ISBT-128 2D: Aztec, Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC 39
Accessories/Supplies	
Included in the Box	Belt Strap, Battery (XM7-20), Smart Battery (XM7-30, XM7-40), AC/DC Adapter, Power Cord, Media Disks (Inner Core: 12 mm)
Options & Accessories	Soft Case, Shoulder Strap, Battery, Smart Battery, AC/DC PD Adapter, Single/Quad Battery Charger, Single/Quad Docking Cradle (Optional Ethernet), Vehicle Adapter, RAM Mount Vehicle Holder, Serial Cable (Optional Fixed) (D-Sub 9P(M)-14P, 1 m), USB Cable (Optional Fixed) (A-14P, 1 m), USB Cable (A-C, 1 m / C-C, 1 m)
Compatible Supplies	B-linerless™
RFID	
Frequency	UHF, 865 to 928 MHz
Transmit Power	1W
Modulation	ASK
Protocol	ISO 18000-63 (EPC Class1 Gen2V2)
Auto Cutter	-
Tag Pitch	Min 16 mm

Product and Services Portfolio

Applications	XT6-40NR, XT5-40NR	XD5-40lItR, XD5-40tR	XM7-40R
Inventory Accuracy & Visibility	●	●	●
Loss Prevention	●	●	●
Omnichannel Fulfillment	●	●	●
Customer Experience		●	●
Parcel & Pallet Tracking	●	●	●
Supply Chain Visibility	●	●	●
Compliance & Security	●	●	●
Receiving / Put-away Efficiency	●	●	●
Inventory & Material Management	●	●	●
Work-in-Progress (WIP) Tracking	●	●	●
Quality Control & Traceability	●	●	●
Tool & Equipment Tracking	●	●	●
Patient Safety & Identification		●	●
Inventory Control	●	●	●
Quality Care		●	●
Pharmaceutical & Specimen Tracking	●	●	●
Asset Tracking	●	●	●
Security & Compliance	●	●	●
Field Operations	●	●	●
Book Identification	●	●	●