

CITIZEN

Safer label printing with self-protective housing.

Safer. Cleaner. Printers.



Self-protective housing and disinfectant ready

The CL-H300SV was not only designed to withstand the harsh chemicals of disinfection products but to stop bacteria in its tracks too. The technology within the casing and the printer itself has an SIAA mark fulfilling ISO 22196 which further reinforces that it is engineered to deliver effective results against bacteria growth and are designed to the highest industry standards.

Compact

The small footprint of the CL-H300SV makes it a perfect printer for tight spaces but still allows labels up to 4.5 inches wide to be printed on a 5 inch media roll.

Connected

The CL-H300SV provides users with flexible connection options including USB as standard with optional Bluetooth, Wireless LAN, Ethernet and USB Hosts + LAN interface cards.

CL-H300SV

Label, Desktop

Applications

- Healthcare
- Hospitality
- Kitchen
- Pharmacy
- Retail



Matches with the aesthetics and technology of CT-E601 POS printer

TOMORROW'S PRINTING TODAY

Citizen Systems Europe GmbH, Waterfront, Lotus Park, Staines-Upon-Thames, TW18 3AG, United Kingdom, +44 20 8893 1900

CITIZEN SYSTEMS EUROPE GMBH



USB interface model with optional Bluetooth, Wireless LAN, Ethernet and USB Hosts + LAN interface cards

Specifications

Model	CL-H300SV
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	8 inches per second (200 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 - 4.6 inches (25 - 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 190 µm
Media Sensor	Fully adjustable gap and reflective black mark
Main Interface	Dual interface USB built-in plus optional interface card slot
Optional interfaces	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Serial (RS-232C compliant), Ethernet (SEH), Bluetooth with Apple™ MFi compatibility
Emulations (Languages)	Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2® , Datamax® DMX, Eltron® EPL2® , CBI™ BASIC Interpreter, EPL-2®
Drivers and software	Free-of-charge from website, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Warranty	2 Years, 30 Kms or 6 months


All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CL-H300SV

Label, Desktop

Features & Benefits

- Paper load: Hi-Lift™ mechanism and ClickClose™ closure
- Printing Speed: Ultra fast print out - up to 200mm per second (8 inches per second)
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Small footprint



Stylish, modern and compact design