



Simple design, intuitive operation

The CMP-40L is designed like all Citizen printers to be simple to use and easy to operate.

High capacity media rolls

The CMP-40L printer can accept media rolls with a diameter of approximately two inches. It supports label printing via the integral label-gap sensor as well as receipts.

Robust

The durable, strong moulded plastic case is IP54 rated and can withstand drops of 1.8 metres meaning your printer will keep running and running.

Applications

- Logistic / Transport
- Law Enforcement
- Ticketing
- Warehousing



LCD display for easy configuration and operation

Specifications

Model	CMP-40L
Resolution	203 dpi
Print Speed (maximum)	3 inches (80 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	50 - 112 mm
Roll Size (max), Core Size	Diameter 2.28 inches (58 mm)
Media Sensor	Gap, reflective black mark and paper end
Main Interface	Dual Interface Serial (RS-232 /mini DIN connector), USB (mini B connector)
Optional interfaces	Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN
Environmental rating, drop test	Exceeds IP54. Survives multiple drops of 1.8 metres
Battery type and capacity	Hard pack 7.4V 2600mAh
Emulations (Languages)	ESC/POS™ , CPCL™ compatibility, Zebra® ZPL2®
Size (W x D x H) and Weight	164 x 174 x 80 mm, 1 Kg (with battery)

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CMP-40L

Other

Features & Benefits

- Paper load: Quick and easy media changing - drop-in paper loading
- Display: LCD display for easy configuration and operation
- Mobile-POS ready
- Mains charger included
- Standard clip-in battery
- Additional batteries
- External battery charger
- Soft cases and shoulder straps
- USB and Serial cables
- Magnetic Strip Reader: Factory option. ISO 7811/2, JIS standards. Dual track (1+2+3), 10-15 cm/s swipe speed
- Smart Card Reader (IC Card): Factory Option. 9,600 bps read speed, internal 1-channel
- Car adapter



Easy media loading with dropin paper loading and paper out indicators