



Gprinter GP-1125T

Карточка: <https://autoidvision.ru/catalog/gprinter-gp-1125t>

Источник данных: <https://gainscha.com.tw/product/112.html>

Характеристики	
Printer Model	GP-1125T
Print Method	Thermal Transfer / Direct Thermal
Print Speed(inch/s)	2~5 inch/s
Interface	Serial+USB+Parallel+Ethernet
Print Resolution	203 DPI
Print Density	0.125×0.125 mm (1 mm = 8 dots)
Print Width	104 mm(4.25")
Print Length	2286 mm(90")
Print Head	50KM
Printer Dimensions	285mm(L) x 210mm(W) x 180mm(H)
Print Weight	2.09KG
Memory	Flash: 4MB RAM: 8MB
Font Size	Font 0 to Font 8
Power supply	Input: AC 100-240V, 50~60Hz Output: DC 24V 2.5A
Media Roll Diameter	Inside:127mm(5") Max. Outside:214mm(8.4") Max.
Media Width	120 mm(4.72") Max. ; 20 mm(0.78") Min.
Media Roll Core Size	25.4 mm~38 mm(1"~1.5")
Media type	Continuous paper, label paper with gap, fan fold label paper, blackmark paper
Media rolling up method	Printing side outward rolling / inward rolling
Media Length	10~2286mm(0.39"~90")
Ribbon Diameter	67mm Max.
Ribbon Length	300m Max.
Ribbon Core Size	1 inch (25.4 mm)
Ribbon Width	110 mm Max. 30 mm Min.
Enlargement&Rotation	1 to10 times enlargement in both directions; 0°、90°、270°、360°rotation
Work environment	Temperature 5~45°C (41~113°F), humidity 25~85%
Storage environment	Temperature -10~50°C (14~122°F), humidity 10~90%
Emulation	TSPL

