


iX6P

Wide Industrial Barcode Overprinter



- Printing speed is up to 12 ips
- Automatically recognize 203 dpi and 300 dpi resolutions without relying on PC settings
- Free software BarTender can easily edit labels
- Support international general barcode specifications
- It has a variety of interfaces, serial port, B-type USB, Ethernet port as standard, and WiFi as optional



Model	iX6P
Print Method	Direct thermal/Thermal transfer
Resolution/Maximum printing speed	203 dpi/12 ips Optional 300 dpi/8 ips
Max. Print Length	3121mm(203 dpi) 1387mm(300 dpi)
Max. Print Width	168 mm
Print Protocol	ZPL,DPL,EPL,TSPL
Supplies Types	Continuous label paper, gap label paper, black mark label paper, perforated paper, environmental friendly thermal label paper, super coated paper, PP/PVC/PET/BOPP coated label paper, synthetic fiber label paper, textile belt
Supplies Diameter	3-inch inside diameter, maximum 8-inch outside diameter
Supplies Thickness	80 μm-254 μm
Supplies Width	50.8mm-175mm
Ribbon Types	Wax,Resin,Wax/Resin
Ribbon Core	1 inch
Ribbon Width	58mm-172mm
Ribbon Length	450m
Sensors	Cover Opening Sensor, Out-of-Ribbon Sensor, Out-of-paper Sensor,Thermal Head Temperature Sensor, Gap/Hole mark/Black mark Sensor, Motor Temperature Sensor
Standard Interfaces	1 Type-B USB, 3 USB HOST, 1 Ethernet port, 1 RS232 Serial port
Optional Interfaces	Wi-Fi
RAM	512MB
Flash	256MB
Operation Interfaces	4 status lights, 6 keys, 1 3.5-inch color touch screen
Dimension(L*W*H)	460.4 X 322 X 330.5mm
Weight	14.5KG
Safety Regulations	CE, FCC, CCC, CB, UL, RoHS, WEEE

