



## iDPRT T-230

Карточка: <https://autoidvision.ru/catalog/idprt-t-230>

Источник данных: <https://www.idprt.com/Products/T-230-Portable-Thermal-Transfer-Barcode>

| Характеристики                |                                                                                                                                                                                                                                   |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRINTER MODEL                 | HM-T230                                                                                                                                                                                                                           |
| Resolution                    | 203dpi                                                                                                                                                                                                                            |
| Printing method               | Direct Thermal and Transfer Thermal                                                                                                                                                                                               |
| Max. print speed              | Max.30mm/s                                                                                                                                                                                                                        |
| Max. print width              | 2"(50mm)                                                                                                                                                                                                                          |
| Max. print length             | 39.4"(1000mm)                                                                                                                                                                                                                     |
| Physical dimension(W x H x D) | 8.07"(205mm)x4.35"(110.5mm)x2.95"(75mm)                                                                                                                                                                                           |
| Weight                        | 0.3lbs (0.76kg)                                                                                                                                                                                                                   |
| Processor                     | 32-bit RISC CPU                                                                                                                                                                                                                   |
| Memory                        | 8MB Flash /16MB RAM                                                                                                                                                                                                               |
| Interface                     | Standard:USB Type-C, NFC, Bluetooth4.0/BLE ; Optional: Wi-Fi 802.11a /b/g                                                                                                                                                         |
| Power                         | Battery:2500mAh ; Input: AC 100~240V, 2.0A, 50~60 Hz ; Output: DC 5V 2A, 10W                                                                                                                                                      |
| User interface                | 2operation button( power,feed ) ; 0.96" LCD                                                                                                                                                                                       |
| Sensors                       | Out-of-paper sensor, ; Gap sensor, Cover opening sensor, ; Battery voltage detectio                                                                                                                                               |
| Graphic formats               | PCX,BMP                                                                                                                                                                                                                           |
| Printer Language              | CPCL                                                                                                                                                                                                                              |
| Media type                    | Wire label, art paper, silver polyester,                                                                                                                                                                                          |
| Media handling                | Standard: Continuous, Tear-Off                                                                                                                                                                                                    |
| Media width                   | Min 0.71"(18mm) / Max 1.97"(50mm)                                                                                                                                                                                                 |
| Media thickness               | 0.002"(0.06mm) to 0.010"(0.250mm)                                                                                                                                                                                                 |
| Media max. roll diameter      | 2.56"(65mm)                                                                                                                                                                                                                       |
| Media length                  | Min.: 1"(25mm) ; Max.: 39.4"(100mm)                                                                                                                                                                                               |
| Ribbon length                 | 98.4 ft(30m)                                                                                                                                                                                                                      |
| Environment condition         | Operating Temperature: 41° to 104°F (5° to 40°C) (limitations based on selected media) / Operating Humidity: 25 to 85% RH Non-Condensing ; Storage Temperature: -20° to 122° F (-20° to 50° C) / Storage Humidity: Non-Condensing |
| Safety Certification          | CCC, FCC, CE, CB, SRRC                                                                                                                                                                                                            |
| Environmental concer          | RoHS                                                                                                                                                                                                                              |

Характеристики приведены по данным страницы производителя на дату составления; официального PDF-даташита вендор не публикует. Оформлено AutolD Vision, 22.09.2026. Актуальные артикулы, аксессуары и аналоги — на карточке модели IDPRT T-230  
AutolD Vision autoidvision.ru