


POWERFUL AND EASY TO USE 2 INCH PORTABLE PRINTER

- Compact and rugged design
- IP42, IP54(with case) certified :
protection against dust and water
- Drop resistance : 1.2M onto concrete
- Large capacity of paper roll up to 56mm(OD)
- Adjustable paper width from 25.4 to 58mm
- Flexible connectivity including RS-232C, USB,
Bluetooth or Wi-Fi(802.11b/g)
- Prints at 80mm per second
- Fast AC/DC charger and long life battery :
3.7Hrs charging time, 25Hrs stand-by
- Optional accessories : leather case, shoulder strap,
cradle and vehicle charger(12/24V)



DIMENSION : 104mm x 154mm x 74mm (W x D x H)

WEIGHT : 490g (with Battery)

SPECIFICATION

PRINT METHOD		Direct Thermal
PRINTING SPEED (max)		80mm/sec
DOT DENSITY		203 DPI
DOT PITCH		8dots/mm, 0.125 pitch
EFFECTIVE PRINTING WIDTH		48mm, 384dots/line
PAPER	TYPE	Thermal paper / Label
	WIDTH	25.4mm ~ 57.5±0.5mm
	THICKNESS	0.06mm ~ 0.16mm
	ROLL DIAMETER	Max. Ø 56.0mm
	ROLL CORE INNER DIAMETER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	50,000,000pulse or more
FONTS and GRAPHICS	STANDARD FONTS	Seven resident fonts 12-48 pt.
	OPTIONAL	International Character Sets
	GRAPHICS, LINE AND BOX DRAWING	PCX and Bitmap
BARCODE	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)	

LK-P11



EMULATION	ESC/POS, CPCL Command compatible	
DRIVER	Windows Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows(CE 4.2 & 5.0 / Mobile 5.0-), Linux Printer Driver, Symbian, Blackberry, Android (2.1-)	
SENSOR	Paper end / Black mark / Gap / Cover open sensors	
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi(802.11b/g)
BATTERY CHARGER	External Charger(Output 8.4VDC/0.8A)	
BATTERY	7.4V 2200mAh Li-ion, 3.7Hrs Charging Time 25Hrs stand-by	
DIMENSION	WxDxH(mm)	104 x 154 x 74
	WxDxH(inch)	4.0 x 6.0 x 2.9
WEIGHT	490g (with Battery)	
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 95%
	STORAGE	10 ~ 95%