

Mobile Printer

LK-P30

3 Inch Thermal Mobile Printer

- Direct thermal receipt / Label mobile printer
- High speed(Max 100mm/sec)
- USB, RS-232C, Bluetooth, Wi-Fi interface
- Support text and graphic printing
- Easier paper roll loading
- High resolution (203dpi)
- Adjustable paper width (25mm ~ 80mm)
- Support magnetic stripe reader & smart card reader



LKP SERIES SPECIFICATION

LUKHAN®

MODEL		LK-P30
PRINT METHOD		Direct Thermal
PRINTING SPEED		100 mm/sec
DOT DENSITY		203 DPI
DOT PITCH		8dots/mm, 0.125 pitch
EFFECTIVE PRINTING WIDTH		72mm, 576 Dots/line
PRINTING DIRECTION		Unidirectional with Friction Feed
CHARACTER PER LINE		Font A(12×24) 48 columns Font B(9×17) 64 columns
PAPER	TYPE	Thermal paper / Label
	WIDTH	25.4 ~ 79.2mm
	THICKNESS	0.065 ~ 0.09 mm
	ROLL DIAMETER	Max. Φ56mm
	ROLL CORE INNER DIAMETER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	1,000,000 pulse or more(12.5% print ratio)
CHARACTER	ALPHA NUMERIC CHARACTER	95
	EXTENDED GRAPHIC	128 *18 page(1 space page)
	INTERNATIONNAL CHARACTER	14
BARCODE		EAN-8, EAN-13, Code39, ITF, UPC-A, Codabar, Code93, Code128, PDF417(2D)
EMULATION		ESC/POS, CPCL
DRIVER		Window(2000, XP 32bit & 64bit, 2003 server 32bit & 64bit, Vista 32bit & 64bit, 2008 server 32bit & 64bit, Embedded for point of service, CE 4.2 & 5.0, mobile 5.0)
SENSOR		Black Mark, Gap, Paper End Sensor, Cover Open Sensor
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth, Wi-Fi
POWER	TYPE	External Charger (100~240Vac)
	BATTERY	7.2V 2200mA, Li-on
DIMENSION	Wmm x Dmm x Hmm	120× 70 × 152
	W" x D" x H"	4.72× 2.75 × 5.98
WEIGHT (With battery)		505g , 615g(With battery)
TEMPERATURE	OPERATING TEMPERATURE	5 ~ 40°C
	STORAGE TEMPERATURE	-20 ~ 60°C
HUMIDITY	OPERATING HUMIDITY	35 ~ 80%
	STORAGE HUMIDITY	10 ~ 90%

Specifications are subject to change without notice.

December 2008

LUKHAN®

SEWOO TECH Co., Ltd.

Doosung Bd, 689-20, Kumsong-dong,
Kunpo-si, Kyunggi-do, 435-862, Korea
Tel : 82-31-459-8200 Fax : 82-31-459-8880
E-mail : sales@miniprnter.com
www.miniprnter.com



www.miniprnter.com