

HN-6208SR

Handheld Barcode Scanner



- High Performance Automatic Decoding Technology.
- Extended DOF, Capable of scanning from different distances.
- Mega Pixel Sensor, Quick, Easy and Accurate Reading, Even on damaged and terrible condition barcode.
- Support Multi Keyboard Languages.
- 1.8 m Drop Test Approved, Best-in-class Durability.
- Completely Compatible with Multi System, Plug-and-Play.



Specification

Model	HN-6208SR
Image Sensor	COMS
Pixel	1280×1080
Illumination	White LED
Aiming	Red LED
Symbologies	2D: PDF417, QR Code, Data Matrix, HanXin, Maxicode ,Postal Codes etc 1D: Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E,UPCA, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5,Industrial 25, Standard 25, Code39, Codabar, Code 93, Code11, Plessey, MSI-Plessey, RSS-14. RSS-Limited. RSS-Expand etc
Resolution	≥3mil
Typical DOF	13mil EAN: 40-550 mm; 3mil Code39: 50 mm-220 mm; 20mil QR: 40-350 mm; 15mil DM: 40-300 mm
Scan Angle	Pitch±60° Tilt360° Skew±60°
FOV	Horizontal: 40 °, Vertical: 30 °
Symbol Contrast	≥20%
Physical Parameter	
Dimension(mm)	93 mm×63 mm×166 mm (L×W×H)
Weight	138 g
Interface	RJ-45 crystal head
Housing Material	PC+ABS
Notification	Buzzer, LED indicator
System Interface	RS-232 serial interface, USB keyboard, USB virtual serial interface
Trigger Method	Keyboard reading, Sensor reading, Continuous reading
Electrical Parameter	
Operating Voltage	5VDC±10%
Operating Current	Standby Current: 80mA; Operating Current: 350mA
Environment Parameter	
Working Temperature	-20~50°C
Storage Temperature	-40~70°C
Humidity	5% to 95% (non-condensing)
Drop Specification	1.8 m
IP rating	IP42
Certificates	CE FCC RoHS

Application



iDPRT Xiamen Hanin Co.,Ltd.

ADD: 5F, 10# Building, Gaoqi South 12 Road, Aide Industrial Pa
TEL: +86-(0)592-5932525 FAX: +86-(0)592-5885992
WEB: www.idprt.com EMAIL: info@idprt.com

rk, Huli District, Xiamen, P.R China



iDPRT Official Website