



Winson WAI-6510

Карточка: <https://autoidvision.ru/catalog/winson-wai-6510>

Источник данных: <https://www.winsonchina.com/products/https-wwwalibabacom-product-detail-winson-wai-6510-2d-cmos-barcode62552184571htmlspma2747manage0046f471d2f0vj1d>

Характеристики	
Тип	1D&2D Image omni-directional desktop (presentation) barcode scanner
Dimensions (L*W*H)	100mm*95mm*158mm (3.94in*3.86in*5.9in)
Weight	265g
Configurations	Decoding
Temp (operation)	0° to 50°C
Temp (storage)	-10° to 60°C
Humidity	5 - 85% (operation), 5 - 85% (storage)
Ambient light	Fluorescent light 4000lx max, direct sun light 80,000lx max, white light 4000lx max
Shock drop test	1.5m drop onto concrete surface
Interface	RS-232 / USB HID KEYBOARD / USB VCP
Voltage requirement	5VDC±10%
Current consumption	Max: 200mA
Photo sensor	CMOS array sensor
Sensor resolution	1280x800 pixels
Aim light source	Red LED
Min resolution	1D: 0.076mm/3mil (PCS 0.9); 2D: 0.152mm/7mil (PCS 0.9)
Min. PCS value	>30% UPC/EAN 13 (13mil)
Field of View	58°(H), 45°(V)
Symbologies 1D	Codabar, Code128, Code39, Code93, Code11, EAN13, EAN8, GS1-Databar, GS1-128 (EAN-128), Interleaved 2 of 5, Matrix 2 of 5, Industry 2 of 5, UPC- A, UPC-E, ISBN, ISSN
Symbologies 2D	PDF417, Data Matrix, QR Code, Micro PDF417, Micro QR Code, Aztec Code

Характеристики приведены по данным страницы производителя на дату составления; официального PDF-даташита вендор не публикует. Оформлено AutolD Vision, 22.09.2026. Актуальные артикулы, аксессуары и аналоги — на карточке модели.

